



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: LSV-600-W-TC-60#KK

DESCRIPTION: **GRAPHIC ARTS**

Laminates and Coated Products Engineered for the Graphic Arts Industry

FEATURES: "Cling" qualities of PVC allow adhesion to most clean, smooth surfaces without the use of adhesive. PVC is coated with a barrier coat to minimize plasticizer migration and improve printability.

APPLICATION: Ultimate removability. Point of purchase displays. Temporary signs. Seasonal decorations.

CHEMICAL
PROPERTIES: Solvent Resistance: Poor
Water Resistance: Fair
Humidity Resistance: Fair

PROPERTY	VALUE	TEST METHOD
Thickness w/o liner:	0.0055" nominal	ASTM-D-3652
Service Life:	2 years	
Opacity:	Good	
Dimensional Stability:	Fair	
Application Temperature:	50 degrees F. minimum	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	
Service Temperature:	- 40 to 150 deg. F.	

P/N 16301

Date 03/03/10

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance and are not intended for use in determining engineering specifications. Values represent nominal and average values; individual roll values may vary from average values indicated on the datasheet. User is responsible for determining suitability and fitness for use. User assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics